

# AFTERCARE GUIDE

## HOW TO LOOK AFTER YOUR NEW RESIN BOUND SURFACE

---

Thank you for purchasing your fabulous new resin bound surface from us!

Detailed below are some simple steps to ensure you keep your new driveway looking good for years to come. Your resin bound surface is intended to be used for both foot traffic and vehicle use and is extremely hardwearing and easy to maintain.

- If for any reason work is taking place near your resin bound surface, it would be advised to cover the area of resin bound to safeguard against damage.
- Heavy objects such as waste skips should not be dragged across the resin bound surface nor should things such as fuel spills or oil be left on the surface as this may cause permanent damage.
- If a spillage occurs simply wipe up and wash off at your earliest convenience.
- To keep the resin bound surface clean, you can hose or wash the surface – a bucket of soapy water and a brush works just fine.
- All projects are treated with a mild weed killer before the resin bound system is applied, if for any reason moss or weeds appear on the surface a weed killing agent can be applied with a watering can directly onto the resin bound surface. The weed killer will then drain through the resin bound system naturally to kill off the weeds.
- If there is severe moss build up due to tree's etc, apply two coats of weed killer and wash off appropriately, always follow the manufacturers guidelines.
- Areas that need to be replaced due to damage can be done using the same blend as the original surface, but dependent on the age of the existing surface a patch will take time to match the existing colour. Please note the stone used in the resin bound system is mined from a rock stone face. Some minor colour variation may occur.
- The removal of ice and snow can be achieved by either a plastic shovel or a de-icing salt. Cement or concrete marks can be removed with the careful use of dilute hydrochloric acid; this must be immediately washed off after use.
- A resin rejuvenator can be applied to any resin bound surface to bring a shine back to the surface, if desired.
- Your new resin surface may not be as non-slip when wet after it is freshly laid; this is because there is a clear film of resin sat on the surface, which does wear off with natural weather conditions.

Enjoy your purchase for years to come.



IF YOU HAVE ANY FURTHER QUESTIONS,  
PLEASE DON'T HESITATE TO CALL  
OUR TEAM ON 0800 011 4628  
OR EMAIL [HELLO@A-GRADERESIN.COM](mailto:HELLO@A-GRADERESIN.COM)